

WHITE GLOSS SELF ADHESIVE VINYL

-----Technical Data Sheet -----

Code No.: EVG - x
Description: Qualified white glossy PVC surface with transparent adhesive. Offered with a liner of single side PE-coated release paper.
Surface: 100±10um monomeric white glossy PVC film.
Adhesive: 20±3um transparent adhesive-permanent.
Liner: 120±5gsm single side PE-coated white wood-pulp paper.
Durability: Outdoor use up to 1 year.

Compatible Ink: UV Ink/ Eco Solvent Ink/ HP Latex Inks.

Features: Suitable for variety of printers

Applications: Widely used for storefront window, floor graphics, vehicle wraps, boards and other smooth substrates.

Size: 1070/ 1270 /1370/1520MM *50M

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.100MM ± 0.005MM
Adhesive Thickness	ZC/QR08	0.020MM ± 0.003MM
Liner Thickness	ZC/QR08	0.130MM ± 0.010 MM
Surface brightness	ZC/QR08 Tested by D60 standard Photometric apparatus;	55±5GS
Adhesive Force	ZC/QR08	1.250± 18% kg
Release Force	ZC/QR08	0.015± 0.005kg
Initial Tack	20Minutes in the standard lab	≤Ball No.5
Test Temperature		25 ± 2°C, 65% ± 15%RH
Application Temperature		10°C-35°C 30%-70%RH
Storage Temperature		10°C-35°C 30%-70%RH

▲ Important Notice:

The information and typical values shown are based on an ongoing process of research and development undertaken by our manufacturing partner. The values listed herein are only reference value only. The information herein are subject to change without notice and ATECH shall not be liable for any such changes. This does not constitute a warranty or in any manner whatsoever.

Customers' improper usage may result in destruction and loss of materials. ATECH cannot be held liable for inaccurate representation made with respect to ATECH products. For further information, please visit our website www.atech.co.uk/aboutus.php

Email to enquiries@atech.co.uk